



SIL-370 NT



72 Cell Monocrystalline PV Module



Intertek



Intertek



Fraunhofer
ICF



CEC
LISTED

CHUBB®

* Chubb provides error and omission insurance to Silfab Solar Inc.

INDUSTRY LEADING WARRANTY


All our products include an industry leading 25-year product workmanship and 30-year performance warranty.

35+ YEARS OF SOLAR INNOVATION

Leveraging over 35+ years of worldwide experience in the solar industry, Silfab is dedicated to superior manufacturing processes and innovations such as Bifacial and Back Contact technologies, to ensure our partners have the latest in solar innovation.

NORTH AMERICAN QUALITY

Silfab is the leading automated solar module manufacturer in North America. Utilizing premium quality materials and strict quality control management to deliver the highest efficiency, premium quality PV modules 100% made in North America.



■ BAA / ARRA COMPLIANT

Silfab panels are designed and manufactured to meet Buy American Act Compliance. The US State Department, US Military and FAA have all utilized Silfab panels in their solar installations.

■ LIGHT AND DURABLE

Engineered to accommodate low load bearing structures up to 5400Pa. The light-weight frame is exclusively designed for wide-ranging racking compatibility and durability.

■ LOWEST DEFECT RATE

Total automation ensures strict quality controls during the entire manufacturing process at our ISO certified facilities.

■ DOMESTIC PRODUCTION

Silfab Solar manufactures PV modules in two automated locations within North America. Our 500+ North American team is ready to help our partners win the hearts and minds of customers, providing customer service and product delivery that is direct, efficient and local.

■ SLEEK DESIGN

Sleek design in silver frame with white backsheet.

■ PID RESISTANT

PID Resistant due to advanced cell technology and material selection. In accordance to IEC 62804-1.

Electrical Specifications		SIL-370 NT mono PERC	
Test Conditions		STC	NOCT
Module Power (Pmax)	Wp	370	281
Maximum power voltage (Vpmax)	V	38.9	35.0
Maximum power current (Ipmax)	A	9.6	8.0
Open circuit voltage (Voc)	V	47.6	44.1
Short circuit current (Isc)	A	10.2	8.4
Module efficiency	%	18.8	17.7
Maximum system voltage (VDC)	V	1000	
Series fuse rating	A	20	
Power Tolerance	Wp	0 to +10	

Measurement conditions: STC 1000 W/m² • AM 1.5 • Temperature 25 °C • NOCT 800 W/m² • AM 1.5 • Measurement uncertainty ≤ 3%
• Sun simulator calibration reference modules from Fraunhofer Institute. Electrical characteristics may vary by ±5% and power by 0 to +10W.

Temperature Ratings		SIL-370 NT mono PERC	
Temperature Coefficient Isc		0.03 %/°C	
Temperature Coefficient Voc		-0.3 %/°C	
Temperature Coefficient Pmax		-0.38 %/°C	
NOCT (± 2°C)		45 °C	
Operating temperature		-40/+85 °C	

Mechanical Properties and Components	SIL-370 NT mono PERC	
	Metric	Imperial
Module weight	21.5 kg ±0.3 kg	47.4 ±0.6 lbs
Dimensions (H x L x D)	1992 mm x 994 mm x 38 mm	78.4 in x 39.1 in x 1.5 in
Maximum surface load (wind/snow)*	2400 Pa rear load / 5400 Pa front load N/m²	50.13/112.8 lb/ft^2
Hail impact resistance	Ø 25 mm at 83 km/h	Ø 1 in at 51.6 mph
Cells	72 - Si mono PERC - 5 busbar 158.75 x 158.75 mm	72 - Si mono PERC - 5 busbar 6.25 x 6.25 Inch
Glass	3.2 mm high transmittance, tempered, DSM anti-reflective coating	0.126 in high transmittance, tempered, DSM anti-reflective coating
Cables and connectors (refer to installation manual)	1200 mm, Ø 5.7 mm, MC4 compatible	47.2 in, Ø 0.22 in ,MC4 compatible
Backsheet	Highly reflective white backsheet	
Frame	Anodized Aluminum (Silver)	
Bypass diodes	3 diodes-30SQ045T (45V max DC blocking voltage, 30A max forward rectified current)	
Junction Box	UL 3730 Certified, IP67 rated	

Warranties		SIL-370 NT mono PERC			
Module product workmanship warranty		25 years**			
Linear power performance guarantee		30 years			
		≥ 97% end 1 st year	≥ 90% end 12 th year	≥ 82% end 25 th year	≥ 80% end 30 th year

Certifications		SIL-370 NT mono PERC			
Product		ULC ORD C1703, CEC listed, IEC 62716 Ammonia Corrosion; IEC61701:2011 Salt Mist Corrosion Certified, UL Fire Rating: Type 1			
Factory		ISO9001:2015			

- Modules Per Pallet: 25
- Pallets Per Truck: 30
- Modules Per Truck: 750

*⚠ Warning. Read the Safety and Installation Manual for mounting specifications and before handling, installing and operating modules.

**12 year extendable to 25 years subject to registration and conditions outlined under "Warranty" at www.silfabsolar.com.

Third-party generated pan files from Fraunhofer-Institute for Solar Energy Systems ISE are available for download at: www.silfabsolar.com/downloads



Silfab Solar Inc.
240 Courtneypark Drive East
Mississauga ON L5T 2Y3 Canada
Tel +1 905-255-2501 | Fax +1 905-696-0267
info@silfabsolar.com | www.silfabsolar.com

Silfab Solar Inc.
800 Cornwall Ave
Bellingham WA 98225 USA
Tel +1 360-569-4733

