



Q.HOME⁺ ESS HYB-G1

MODULAR ENERGY STORAGE SOLUTION
FOR NORTH AMERICA



**HYBRID
INVERTER**



**BATTERY
CHARGER**



**LITHIUM-ION
BATTERY**



**10 YEAR PRODUCT
WARRANTY**



SCALABLE SOLUTION FOR OPTIMIZED CONSUMPTION

Scalable storage capacity from 4.5kWh up to 18.9kWh to suit all consumption cases.



SMART DESIGN

Modular design for easy and fast installation, remote control operated hybrid system with PV inverter, lithium-ion battery, and battery charger.



REMOTE MONITORING

Easy maintenance due to its early error detection function, web and mobile monitoring, and a reliable service network.



SAFETY AND RELIABILITY

Premium quality lithium-ion.



DURABILITY

High durability with 10 year product warranty and 90% depth of discharge (DoD).



100% BACKUP POWER FUNCTION

Thanks to the integrated backup power function, even in the event of power failure 100% of the rated inverter output will support critical loads.

THE IDEAL SOLUTION FOR:



Rooftop arrays on residential buildings

TECHNICAL SPECIFICATIONS

| GENERAL PRODUCT INFORMATION | | Q.HOME® ESS HYB-G1 | | | |
|---|-------|--|---------|------------|------------|
| | | 6.0kW | 7.0kW | 7.6kW | 8.6kW |
| Dimensions inverter / storage (L × W × D) | [in] | 36 × 22 × 10.9 (91.3 × 56.0 × 27.6mm) / 18.3 × 7.6 × 23.1in (464 × 193 × 588mm) | | | |
| Weight inverter / storage (4.5kWh) / storage (6.3kWh) | [lbs] | 130 (58.9kg) / 124.8 (56.6kg) / 148.4 (67.5kg) | | | |
| Operating temperature inverter / storage | [°F] | -4 ~ 140 (-20 ~ 60°C) / -22 ~ 167 (-30 ~ 75°C) | | | |
| Relative humidity | [%] | 0-100 | | | |
| Enclosure rating | | Type 4X | | | |
| Mounting | | Wall mounted | | | |
| Max. operating height without power loss | [m] | 2000 | | | |
| Cooling method | | Natural | | | |
| Product warranty / Performance warranty | | 10 / 10 years | | | |
| Noise emissions | [dB] | ≤ 35 | | | |
| AC over voltage category | | I / IV | | | |
| Front panel display | | LCD | | | |
| Communications | | RS485 / LAN / CAN 2.0 / WiFi / 4G (optional) / RF (optional) | | | |
| Remote monitoring | | Web, mobile | | | |
| Software update | | Local USB / Remote Web | | | |
| Energy management system | | Integrated | | | |
| PV DATA (DC) | | | | | |
| Max. input power | [kWp] | 7.2 | 8.4 | 9.12 | 10.32 |
| Max. input voltage [V _{DC}] | [V] | 600 | | | |
| Start input voltage / MPPT operating range / Rated input voltage | [V] | 150 / 105-500 / 360 | | | |
| Shutdown voltage | [V] | 80 | | | |
| Number of independent MPPTs | | 2 | 3 | 3 | 4 |
| Maximum DC power per MPPT | [kWp] | 3.6 | | | |
| Max. input current per MPPT / Max. short circuit current per MPPT | [A] | 10 / 12.5 | | | |
| GRID DATA (AC) | | | | | |
| Max. output power / Rated output power | [kW] | 6.6 / 6 | 7.7 / 7 | 8.36 / 7.6 | 9.46 / 8.6 |
| Nominal voltage / Range | [V] | 120 / 240 split phase (105.5 / 211 ~ 132 / 264) | | | |
| Nominal grid frequency / Range | [Hz] | 60 / 59.3 ~ 60.5 | | | |
| Nominal current | [A] | 25 | 29 | 32 | 36 |
| Power factor | | > 99 (adj. ±0.8) | | | |
| Total harmonic distortion | [%] | ≤ 3 | | | |
| BACKUP POWER OUTPUT (AC) | | | | | |
| Max. output power / Rated output power | [kW] | 6.6 / 6 | 7.7 / 7 | 8.36 / 7.6 | 8.36 / 7.6 |
| Max. continuous output current | [A] | 25 | 29 | 32 | 32 |
| Rated voltage / Range (L-N) | [V] | 120 / 240 split phase (117 / 234 ~ 123 / 246) | | | |
| Rated frequency / Range | [Hz] | 60 | | | |
| Switchover time to backup power | | < 100ms | | | |
| Support by PV during backup power operation | | YES | | | |
| EFFICIENCY | | | | | |
| Max. efficiency (PV-AC) / CEC efficiency | [%] | 96.7 / 95.67 | | | |
| Max. efficiency (PV-Battery) / (Battery-AC) | [%] | 98.24 / 96.46 | | | |
| BATTERY DATA (DC) | | | | | |
| Battery technology | | Lithium-ion (NMC) | | | |
| Battery usable capacity per module | [kWh] | 4.5 / 6.3 | | | |
| Scalability | | Up to three battery modules | | | |
| Max. battery usable capacity | [kWh] | 13.5 / 18.9 | | | |
| Rated power / Max. power (per module) | [kW] | 2.5 / 3.0 | | | |
| Max. battery power | [kW] | 7.5 | | | |
| Rated battery voltage / Battery voltage range (per module) | [Vdc] | 100.8 / 85 ~ 118 | | | |
| Battery Management System voltage range | [Vdc] | 84 - 432 | | | |
| Discharging current | [A] | 25 | | | |
| Depth of discharge (DoD) | [%] | 90 | | | |
| COUNTRY AVAILABILITY / CERTIFICATES AND WARRANTY | | | | | |
| Inverter certificates | | UL 1741, UL 1741.SA, UL 9540, IEEE 1547, IEEE 1547.1, CSA - C 22.2N.107.1-01, UL 1998, UL 1699B, FCC part 15 Class B | | | |
| Battery certificates | | UL 1642, UL 1793, CE, RCM, TUV (IEC 62619), UN 3480, Class 9, UN 38.3 | | | |
| Warranty | | 10 years | | | |

NOTE: Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Hanwha Q CELLS America Inc.

400 Spectrum Center Drive, Suite 1400, Irvine, CA 92618, USA | [TEL +1 949 748 59 96](tel:+19497485996) | [EMAIL inquiry@us.q-cells.com](mailto:inquiry@us.q-cells.com) | [WEB www.q-cells.us](http://www.q-cells.us)

